## T7 Plus

19-key integrated terminal simpler and easy-to-use









## Lead with the next-generation T7 terminal:

- Delivers all the functionality of a T7 Plus with an ATM-style keypad
- Provides more promotional real estate with optional 3-inch printer
- Easier to use as customer-facing PIN device
- Supports fast online authorizations
- Available with optional 35-key traditional keyboard



# T7 Plus

19-key integrated terminal - simpler and easy-to-use

### **Delivers Fast Authorizations**

The Hypercom® T7*Plus* builds on the heritage of Hypercom's popular T7 family of terminals. This newest model is designed for merchants requiring a compact countertop POS terminal accepting all magnetic stripe cards and delivering fast online transaction authorizations.

### "The Clam That Won't Jam"

The revolutionary SureLoad™ printer prints in half the time of previous-generation printers. And it allows paper rolls to simply be dropped in place without feeding through slots and rollers. It also supports longer paper rolls for fewer paper changes and its see-through paper holder alerts cashiers to low conditions before running out of paper in the middle of transactions.

## Supports All Card Types

The T7 Plus supports magnetic stripe and smart cards and is EMV4.0-certified. Its 19-key keyboard initiates daily functions and transactions with a familiar, ATM look and feel.

#### World Headquarters/ North America

Hypercom Corporation 2851 W. Kathleen Road Phoenix, Arizona 85053

Tel: +1.602.504.5000 Fax: +1.602.866.5380

#### Latin America

Hypercom Industria e Comercio LTDA Centro Empresarial Atibaia Rodovia Dom Pedro I, KM 87, 5 Av. Tegula, 888-Ponte Alta Atibaia 12940-000, Brazil Tel: +55.11.4417.7000 Fax: +55.11.4417.7060

#### Asia/Pacific Rim

Hypercom Asia Ltd. 21/F Metro Centre II 21 Lam Hing Street Kowloon Bay, Kowloon Hong Kong Tel: +85.2.2561.6800 Fax: +85.2.2561.5890

#### Europe/Middle East/Africa

Hypercom EMEA, Inc. Unit 2, Woking Eight Woking, GU21 5SB, United Kingdom Tel: +44.1483.718600 Fax: +44.1483.718601

©2004 Hypercom Corporation, all rights reserved. Hypercom and the Hypercom logo are registered trademarks of Hypercom Corporation. SureLoad is a trademark of HypercomCorporation. All other products or services mentioned in this document are trademarks, service marks, registered trademarks or registered service marks of their respective owners.

Celebrating 26 years of technology excellence, innovation and leadership, Hypercom Corporation is a leading global provider of electronic payment solution that add value at the point-of-transaction for consumers, merchants and acquirers, and yield increased profitability for its customers.

Widely recognized as the global payment technology innovator, Hypercom delivers comprehensive card payment terminal, network and server solutions that help merchants and financial institutions generate revenues and increase profits

Headquartered in Phoenix, Arizona, Hypercom's card payment terminal, network and server solutions are leading the transformation of electronic payments in more than 100 countries

## **Specifications:**

Display

LCD: 2 lines x 20 characters (standard), 4 lines x 20 characters (optional); backlight reliable to 50,000 hours (half-life calculated)

Elastomeric; 19 keys, water splash-resistant; 35 keys, 3 soft keys (optional); reliable to 500,000 keystrokes (calculated)

Card Reader

Magnetic stripe: Tracks 1, 2 (standard), Tracks 1, 2, 3 (optional); reliable to 400,000 reads (calculated) Smart Card Reader: EMV4.0 certified; ISO 7816; non-captive; 3V and 5V cards; four 5V SAMS

Communications

Modem: 56k (optional); 1200, 300 bps (standard); synchronous (SDLC) & asynchronous; 2400 bps (optional) PIN pad port: RS-422 4-wire, compatible with S7C, S7SC, S8, S9, S9C, S9SC; LAN: RS-485 multi-drop 2-wire; 10Base-T Ethernet (optional): Peripheral port: RS-232

Printer

SureLoad clamshell design, drop-in loading, thermal technology, 384 dots per line, paper roll 57 mm wide x 80 mm diameter

Memory RAM:1.0 MB (standard) RAM backup: 5-year battery EPROM: 32 KB

AC: 100-240 V, 50/60 Hz DC: 24 V, 1 A

Security

Visa PED approved; Physical: Intrusion detection, encryption

PIN Encryption: DES: PIN-ANSI 9.8, MAC-ANSI 9.9, ANSI x 9.52, Triple DES **Key Management:** Master/session keys (12)

Footprint

10.0 in x 5.18 in x 2.5 in/25.4 cm x 13.2 cm x 6.35 cm

1.5 lbs/0.68 kg approximate

Environment

Temperature: 0-45°C/32-110°F Humidity: max 85%, non-condensing ESD: 12,000 volts

Reliability

80,000 hours (MTBF calculated), excluding printer

Specifications subject to change without notice.

940439-001

